

Faip presents a complete range of high pressure washers with a nice design, easy to transport and suitable for all cleaning applications. Faip high pressure washers are powerful and equipped with the necessary accessories for all possible cleaning tasks. Faip high pressure washer's performances are ranging from 1500 psi – 1,6 GPM to 2900 psi – 5,5 GPM of the professional units. All models of H and F series are based on the high quality Faip axial pump.



**TECHNICAL FEATURES H100 – POWERWASHER – H110:** • Vertical working position. H110 • Complete with: built-in accessories holder, rear hook for electrical cable storage. All models • Axial pump with three steel pistons and light alloy head. • Electric motor with thermal protection. • Detergent delivery with foam lance.

**STANDARD EQUIPMENT All models:** • Spray gun with 17ft hp (high pressure) hose complete with quick screw coupling. • Lance. • Water jet angle adjustment head. • Foam lance.

Code	Model	Remote Control	Max Pressure (bar/psi)	Flow Rate (l/h/GPM)	Temp. Max (°C/°F)	Voltage (PH-V-Hz)	Ab. Power (KW)	Rpm	Detergent Tank L - GAL	Dimensions (cm) - (in)	Weight kg - lb
<b>1-230 - 50</b>											
IDAF84692	H101	By-pass	100/1500	360/1,6	40/104	1-230-50	1,3	2800	0,5-0,13	(37x19x29)- (14,5x7x11)	9-20
IDAF90701	H101DS	Total-Stop	100/1500	360/1,6	40/104	1-230-50	1,3	2800	0,5-0,13	(37x19x29)- (14,5x7x11)	9-20
IDAF49418	H101 PLUS	By-pass	120/1800	360/1,6	40/104	1-230-50	1,8	2800	0,5-0,13	(37x19x29)- (14,5x7x11)	11-24
IDAF90702	H101 PLUS DS	Total-Stop	120/1800	360/1,6	40/104	1-230-50	1,8	2800	0,5-0,13	(37x19x29)- (14,5x7x11)	11-24
<b>1-120 - 60</b>											
IDAF90704	H101 PLUS	By-pass	95/1400	360/1,6	40/104	1-120-60	1,6	3400	0,5-0,13	(37x19x29)- (14,5x7x11)	9-20
IDAF90705	H101 PLUS DS	Total-Stop	95/1400	360/1,6	40/104	1-120-60	1,6	3400	0,5-0,13	(37x19x29)- (14,5x7x11)	9-20

Faip presents a complete range of high pressure washers with a nice design, easy to transport and suitable for all cleaning applications. Faip high pressure washers are powerful and equipped with the necessary accessories for all possible cleaning tasks. Faip high pressure washer's performances are ranging from 1500 psi – 1,6 GPM to 2900 psi – 5,5 GPM of the professional units. All models of H and F series are based on the high quality Faip axial pump.



**TECHNICAL FEATURES H100 – POWERWASHER – H110:** • Vertical working position. H110 • Complete with: built-in accessories holder, rear hook for electrical cable storage. All models • Axial pump with three steel pistons and light alloy head. • Electric motor with thermal protection. • Detergent delivery with foam lance.

**STANDARD EQUIPMENT All models:** • Spray gun with 17ft hp (high pressure) hose complete with quick screw coupling. • Lance. • Water jet angle adjustment head. • Foam lance.

Code	Model	Remote Control	Max Pressure (bar/psi)	Flow Rate (l/h/GPM)	Temp. Max (°C/°F)	Voltage (PH-V-Hz)	Ab. Power (KW)	Rpm	Detergent Tank L - GAL	Dimensions (cm) - (in)	Weight kg - lb
<b>1-230 - 50</b>											
IDAF84690	POWERWASHER	Total-Stop	100/1500	360/1,6	40/104	1-230-50	1,5	3500	0,5-0,13	(23x23x46)- (9x9x18)	5,5-12



# DELFIN

commerciale srl

CFED  
afidcamp Com

Via Cuniberti, 69/E 10151 Torino  
Tel 011 73.29.16 Fax 011 455.15.40  
info@delfincommerciale.it  
www.delfincommerciale.it  
P.Iva 08090130017

**ASPIRATORI INDUSTRIALI  
MACCHINE PULIZIA INDUSTRIALE  
DETERGENZA - IGIENE INDUSTRIALE  
ASSISTENZA TECNICA - RICAMBI  
NOLEGGIO- LEASING TASSO ZERO**



Faip presents a complete range of high pressure washers with a nice design, easy to transport and suitable for all cleaning applications. Faip high pressure washers are powerful and equipped with the necessary accessories for all possible cleaning tasks. Faip high pressure washer's performances are ranging from 1500 psi – 1,6 GPM to 2900 psi – 5,5 GPM of the professional units. All models of H and F series are based on the high quality Faip axial pump.

**TECHNICAL FEATURES H100 – POWERWASHER – H110:** • Vertical working position. H110 • Complete with: built-in accessories holder, frear hook for electrical cable storage. All models • Axial pump with three steel pistons and light alloy head. • Electric motor with thermal protection. • Detergent delivery with foam lance.

**STANDARD EQUIPMENT All models:** • Spray gun with 17ft hp (high pressure) hose complete with quick screw coupling. • Lance. • Water jet angle adjustment head. • Foam lance.

Code	Model	Remote Control	Max Pressure (bar/psi)	Flow Rate (l/h/GPM)	Temp. Max (°C/°F)	Voltage (PH-V-Hz)	Ab. Power (KW)	Rpm	Detergent Tank L - GAL	Dimensions (cm) - (in)	Weight kg - lb
<b>1-230 - 50</b>											
IDAF82550	H100	Total-Stop	110/1650	360/1,6	40/104	1-230-50	1,6	3500	0,5-0,13	(23x23x46)- (9x9x18)	5,5-12
<b>1-120 - 60</b>											
IDAF90706	H100	Total-Stop	90/1300	360/1,6	40/104	1-120-60	1,5	3700	0,5-0,13	(23x23x46)- (9x9x18)	5,5-12



Faip presents a complete range of high pressure washers with a nice design, easy to transport and suitable for all cleaning applications. Faip high pressure washers are powerful and equipped with the necessary accessories for all possible cleaning tasks. Faip high pressure washer's performances are ranging from 1500 psi – 1,6 GPM to 2900 psi – 5,5 GPM of the professional units. All models of H and F series are based on the high quality Faip axial pump.

**TECHNICAL FEATURES H100 – POWERWASHER – H110:** • Vertical working position. H110 • Complete with: built-in accessories holder, frear hook for electrical cable storage. All models • Axial pump with three steel pistons and light alloy head. • Electric motor with thermal protection. • Detergent delivery with foam lance.

**STANDARD EQUIPMENT All models:** • Spray gun with 17ft hp (high pressure) hose complete with quick screw coupling. • Lance. • Water jet angle adjustment head. • Foam lance.

Code	Model	Remote Control	Max Pressure (bar/psi)	Flow Rate (l/h/GPM)	Temp. Max (°C/°F)	Voltage (PH-V-Hz)	Ab. Power (KW)	Rpm	Detergent Tank L - GAL	Dimensions (cm) - (in)	Weight kg - lb
<b>1-230 - 50</b>											
IDAF90703	H110	Total-Stop	120/1800	360/1,6	40/104	1-230-50	1,8	2800	0,5-0,13	(34x32x47)- (13x13x18)	12- 26,5
<b>1-120 - 60</b>											
IDAF90707	H110	Total-Stop	95/1400	360/1,6	40/104	1-120-60	1,6	3400	0,5-0,13	(34x32x47)- (13x13x18)	12- 26,5



Starting from H110 PLUS, all Faip models are equipped with trolley and handle in order to ease the transportation near to the object to be cleaned. The built-in accessory holders and the two hooks for high pressure hose and electrical cable permit to store on the machine itself all the accessories. Faip high pressure washer's performances are ranging from 1500 psi - 1,6 GPM to 2900 psi - 5,5 GPM of the professional units. All models of H and F series are based on the high quality Faip axial pump.

**TECHNICAL FEATURES H110 PLUS** • Axial pump with three steel pistons and light alloy head. • Detergent delivery with foaming generator.

**All models** • Remote controlled AUTOMATIC TOTAL-STOP. • Electric motor with thermal protection. • Vertical working position. • Built-in accessory holder, front hook for hose storage.

**STANDARD EQUIPMENT H110 PLUS** • Spray gun with 17ft hp (high pressure) hose complete with quick screw coupling. • Lance. • Water jet angle adjustment head. • Foam lance.

Code	Model	Remote Control	Pressure (bar/psi)	Max Pressure (bar/psi)	Flow Rate (l/h/GPM)	Temp. Max (°C/°F)	Voltage (PH-V-Hz)	Ab. Power (KW)	Detergent Tank Rpm	Dimensions		Weight
										L - GAL	(cm) - (in)	
<b>1-230 - 50</b>												
IDAF82549	H110 Plus	Total-Stop	110/1650	120/1800	360/1,6	60/140	1-230-50	1,8	2800	0,5-0,13	(34x32x75)- (14x13x30)	12-26
<b>1-120 - 60</b>												
IDAF90712	H110 Plus	Total-Stop	85/1250	95/1400	360/1,6	60/140	1-120-60	1,6	3400	0,5-0,13	(34x32x75)- (14x13x30)	12-26

Starting from H110 PLUS, all Faip models are equipped with trolley and handle in order to ease the transportation near to the object to be cleaned. The built-in accessory holders and the two hooks for high pressure hose and electrical cable permit to store on the machine itself all the accessories. Faip high pressure washer's performances are ranging from 1500 psi - 1,6 GPM to 2900 psi - 5,5 GPM of the professional units. All models of H and F series are based on the high quality Faip axial pump.



**TECHNICAL FEATURES H120 - H130 - H140** • Axial pump with three steel pistons and light alloy head. • Low pressure detergent delivery with control from the lance.

**TECHNICAL FEATURES H130 OT** • Axial pump with three steel pistons and brass head. • Detergent delivery with control from the lance.

**All models** • Remote controlled AUTOMATIC TOTAL-STOP. • Electric motor with thermal protection. • Vertical working position. • Built-in accessory holder, front hook for hose storage.

**STANDARD EQUIPMENT H120** • Spray gun with 23ft hp hose complete with quick screw coupling. • Lance. • Water jet angle adjustment head. • Foam lance.

**STANDARD EQUIPMENT H130 - H140** • Spray gun with 23ft hp hose complete with quick screw coupling. • Lance. • Low/high pressure commutation head, detergent control and adjustable water jet angle.

Code	Model	Remote Control	Pressure (bar/psi)	Max Pressure (bar/psi)	Flow Rate (l/h/GPM)	Temp. Max (°C/°F)	Voltage (PH-V-Hz)	Ab. Power (KW)	Detergent Tank Rpm	Dimensions		Weight
										L - GAL	(cm) - (in)	
<b>1-230 - 50</b>												
IDAF83785	H120	Total-Stop	120/1800	130/1900	410/1,8	60/140	1-230-50	2,1	2800	0,5-0,13	(26x30x86)- (11x12x34)	18-40
IDAF84695	H130	Total-Stop	130/1900	140/2000	450/2,0	60/140	1-230-50	2,4	2800	1-0,26	(26x30x86)- (11x12x34)	18-40
IDAF84694	H130 Test Ott	Total-Stop	130/1900	140/2000	450/2,0	60/140	1-230-50	2,4	2800	1-0,26	(26x30x86)- (11x12x34)	18-40
IDAF84693	H140	Total-Stop	140/2000	150/2200	500/2,2	60/140	1-230-50	2,7	2800	1-0,26	(31x42x89)- (12x17x35)	23-51
<b>1-120 - 60</b>												
IDAF90713	H120	Total-Stop	90/1300	100/1500	340/1,5	60/140	1-120-60	1,5	3400	1-0,26	(26x30x86)- (11x12x34)	18-40



Starting from H110 PLUS, all Faip models are equipped with trolley and handle in order to ease the transportation near to the object to be cleaned. The built-in accessory holders and the two hooks for high pressure hose and electrical cable permit to store on the machine itself all the accessories. Faip high pressure washer's performances are ranging from 1500 psi - 1,6 GPM to 2900 psi - 5,5 GPM of the professional units. All models of H and F series are based on the high quality Faip axial pump.

**TECHNICAL FEATURES H1600** • Axial pump with three steel pistons and light alloy head. • Low pressure detergent delivery with control from the lance.

**All models** • Remote controlled AUTOMATIC TOTAL-STOP. • Electric motor with thermal protection. • Vertical working position. • Built-in accessory holder, front hook for hose storage.

Code	Model	Remote Control	Pressure (bar/psi)	Max Pressure (bar/psi)	Flow Rate (l/h/GPM)	Temp. Max (°C/°F)	Voltage (PH-V-Hz)	Ab. Power (KW)	Detergent Tank Rpm	Dimensions		Weight
										L - GAL	(cm) - (in)	
<b>1-120 - 60</b>												
IDAF90715H1600	Total-Stop		100/1500	110/1600	360/1,6	60/140	1-120-60	1,65	3400	1-0,26	(26x30x86)- (11x12x34)	18-40

Starting from H110 PLUS, all Faip models are equipped with trolley and handle in order to ease the transportation near to the object to be cleaned. The built-in accessory holders and the two hooks for high pressure hose and electrical cable permit to store on the machine itself all the accessories. Faip high pressure washer's performances are ranging from 1500 psi - 1,6 GPM to 2900 psi - 5,5 GPM of the professional units. All models of H and F series are based on the high quality Faip axial pump.



**TECHNICAL FEATURES H1900 - H2000 - H2200** • Axial pump with three steel pistons and light alloy head. • Low pressure detergent delivery with control from the lance.

**TECHNICAL FEATURES H2200 OT** • Axial pump with three steel pistons and brass head. • Detergent delivery with control from the lance.

**All models** • Remote controlled AUTOMATIC TOTAL-STOP. • Electric motor with thermal protection. • Vertical working position. • Built-in accessory holder, front hook for hose storage.

**STANDARD EQUIPMENT H1900** • Spray gun with 23ft hp hose complete with quick screw coupling. • Lance. • Water jet angle adjustment head. • Foam lance.

**STANDARD EQUIPMENT H2200** • Spray gun with 23ft hp hose complete with quick screw coupling. • Lance. • Low/high pressure commutation head, detergent control and adjustable water jet angle.

Code	Model	Remote Control	Pressure (bar/psi)	Max Pressure (bar/psi)	Flow Rate (l/h/GPM)	Temp. Max (°C/°F)	Voltage (PH-V-Hz)	Ab. Power (KW)	Detergent Tank Rpm	Dimensions		Weight
										L - GAL	(cm) - (in)	
<b>1-230 - 50</b>												
IDAF90708H1900	Total-Stop		120/1800	130/1900	410/1,8	60/140	1-230-50	2,1	2800	1-0,26	(29x28x86)- (11,4x11x34)	18,5-40
IDAF90709H2000	Total-Stop		130/1900	140/2000	450/2,0	60/140	1-230-50	2,4	2800	1-0,26	(29x28x86)- (11,4x11x34)	19-42
IDAF90710	H2000 Test Ott	Total-Stop	130/1900	140/2000	450/2,0	60/140	1-230-50	2,4	2800	1-0,26	(29x28x86)- (11,4x11x34)	19-42
IDAF90711H2200	Total-Stop		140/2000	150/2200	500/2,2	60/140	1-230-50	2,7	2800	1-0,26	(29x28x86)- (11,4x11x34)	23,5-52