



The FT series includes many models in order to offer a wide choice of high-pressure washing instruments with all optional accessories. All the models are equipped with automatic Total-Stop and they have a pressure ranging from 1500 to 2900psi; in addition, their solid structure makes them highly professional machines and the accessories contribute to the construction of a modern machine that is suitable for resolving any kind of cleaning problem.

**TECHNICAL FEATURES** • Pump with three ceramic pistons, rod/crank system and forged brass head. In the FT 200/15-4P model, the high-pressure pump head is made of nickel-plated brass. • Remote controlled AUTOMATIC TOTAL-STOP. • Electric motor: four-pole (1450 rpm) in the FT - 4P models, two-pole (2800 rpm) in all the other models. • All are continuous duty, with thermal protection. • Low-pressure detergent delivery with control from the lance.

**STANDARD EQUIPMENT** • Spray gun with heatproof extension. • 26ft high-pressure hose with quick screw couplings. • Double lance fitted with pressure and detergent control. • High-pressure steel nozzle and brass nozzle for chemicals. • Can be fitted with hose winder (optional accessory).

Code	Model	Remote Control	Max Pressure (bar/psi)	Flow Rate (l/h/GPM)	Temp. Max (°C/°F)	Voltage (PH-V-Hz)	Ab. Power (KW)	Rpm	Detergent Tank L - GAL	Dimensions (cm) - (in)	Weight kg - lb
IDAF83085	FT 130/11 M	Total-Stop	120/1750	540/2,4	60/140	1-230-50	2,8	2800	11-2,9	(75x48x88)-(30x19x35)	43-95
IDAF83086	FT 160/14	Total-Stop	150/2200	750/3,3	60/140	3-400-50	4,5	2800	14-3,7	(75x48x88)-(30x19x35)	44-97
IDAF83087	FT 170/16	Total-Stop	150/2200	860/3,8	60/140	3-400-50	5,2	2800	16-4,2	(75x48x88)-(30x19x35)	45-99
IDAF83088	FT 185/18	Total-Stop	170/2550	1050/4,6	60/140	3-400-50	6,5	2800	18-4,8	(75x48x88)-(30x19x35)	46-101
IDAF83089	FT 215/15	Total-Stop	200/3000	860/3,8	60/140	3-400-50	6,5	2800	15-4,0	(75x48x88)-(30x19x35)	46-101
IDAF83090	FT 220/18	Total-Stop	200/3000	1050/4,7	60/140	3-400-50	7,5	2800	18-4,8	(75x48x88)-(30x19x35)	50-110
IDAF83091	FT 130/11-4P M	Total-Stop	100/1500	630/2,8	60/140	1-230-50	2,9	1450	11-2,9	(75x48x88)-(30x19x35)	54-119
IDAF83092	FT 150/14-4P	Total-Stop	150/2200	780/3,5	60/140	3-400-50	4,7	1450	14-3,7	(75x48x88)-(30x19x35)	55-121
IDAF83094	FT 200/15-4P	Total-Stop	200/2900	900/4	60/140	3-400-50	7,5	1450	15-4,0	(75x48x88)-(30x19x35)	61-134