



**DELFIN**  
commerciale srl

CFED  
afidamp Com

Via Cuniberti, 69/E 10151 Torino  
Tel 011 73.29.16 Fax 011 455.15.40  
info@delfincommerciale.it  
www.delfincommerciale.it  
P.Iva 08090130017

**ASPIRATORI INDUSTRIALI  
MACCHINE PULIZIA INDUSTRIALE  
DETERGENZA - IGIENE INDUSTRIALE  
ASSISTENZA TECNICA - RICAMBI  
NOLEGGIO- LEASING TASSO ZERO**



News from FAIP is making the headlines again! Here is one of the latest additions to the company's range of hot water cleaners. Super Indy II is made from carefully selected materials to live up to the expectations of the most demanding cleaning professionals. Just look at the attention to detail and impressive specifications: stainless steel tank, in-line piston pump and motor, pressure adjustment, steam generator adjustment and total-stop remote control.

**TECHNICAL FEATURES ALL MODELS** • Remote control: -By-pass. -Delayed total-stop in the models DS. • Three – ceramic pistons pump with rod/crank system and forged brass head. • Four – pole electric motor (1400 RPM) continuous duty motors with overload thermal switch. • Stainless steel boiler with efficiency >89%. • Pressure adjustment valve and steam production. • High pressure detergent delivery. • Chassis and body: - 2 robust, wide tread rear wheels + 1 swivelling wheel with brake. • 16 litre diesel fuel tank.

**STANDARD EQUIPMENT** • Spray gun with heatproof extension. • High pressure hose. • Lance • High pressure nozzle.

Code	Model	Remote Control	Pressure (bar/psi)	Flow Rate (l/h/GPM)	Temp. Max	Voltage	Ab. Power	Rpm	Detergent Tank	Fuel Tank	Dimensions (cm) - (in)	Weight (kg - lb)
					(°C/°F)	(PH-V-Hz)	(KW)		L - GAL	L - GAL		
IDAC47416	Super Indy II M10	By-Pass	100/1500	600/2,6	30÷140/86÷284	1-230-50	2,2 M	1400	- / -	16 / 4	(100x68x89)-(39x27x35)	120-265
IDAC47417	Super Indy II T15	By-Pass	150/2200	900/4	30÷140/86÷284	3-400-50	4,0 T	1400	- / -	16 / 4	(100x68x89)-(39x27x35)	120-265
IDAC47418	Super Indy II T15 DS	Total Stop	150/2200	900/4	30÷140/86÷284	3-400-50	4,0 T	1400	- / -	16 / 4	(100x68x89)-(39x27x35)	120-265
IDAC47419	Super Indy II T20	By-Pass	200/2900	900/4	30÷140/86÷284	3-400-50	5,5 T	1400	- / -	16 / 4	(100x68x89)-(39x27x35)	120-265
IDAC47420	Super Indy II T20 DS	Total Stop	200/2900	900/4	30÷140/86÷284	3-400-50	5,5 T	1400	- / -	16 / 4	(100x68x89)-(39x27x35)	120-265